

Condor Grass Randweg 14, 8061 RW P.O. Box 21, 8060 AA Hasselt, The Netherlands T (+31) 38 477 89 11 F (+31) 38 477 89 22 E info@condorgrass.com W www.condor-group.eu

Туре	Tufted synthetic grass carpet	
Material	PE Monofilament straight & PP Monofilament curled (UV Stabilized)	
Yarn type	5.000 / 8 dTex PE monofilament straight & 3.000 / 6 dTex PP monofilament curled	
Yarn quality	Environmental friendly, free of lead and cadmium	
Primary backing	100% PP black with fleece, UV Stabilized, Weight 135 gr/m2	
Secondary backing	Black Latex compound with a base of styrenebutadiene (SBR), with drainage holes, Weight 760 gr/m2	
Waterpermeability	60 liter/min/m2	
Pile height	38 mm	
Face weight	1.761 gr/m2	± 10%
Total weight	2.656 gr/m2	± 10%
Tuft gauge	3/8 gauge	
Stitches per 10 cm linear	24	± 1
Stitches per m2	25.200	± 10%
Colour	Mix of light and dark green + Field-Jute thatch	
UV stability	Meets DIN 53387 Standard (6000 hours)	
Colour fastness	Xenon Test: Blue Scale > 7, Grey-scale > 4	
Colour lining	Not Applicable	
Roll width	200 cm, 400 cm	
Roll length	20-25m	
Applications	Gardens, Landscaping	
Infill advice	Silica sand, gradation 0,5 - 1,0 mm, 80% roundshaped, appr. 6 - 8 kg/m2	
Comments	Before installation make sure the rolls are from the same production code (first five digits the roll number) Project.	





