

Condor Grass Randweg 14, 8061 RW P.O. Box 21, 8060 AA Hasselt, The Netherlands

T (+31) 38 477 89 11 F (+31) 38 477 89 22 E info@condorgrass.com W www.condor-group.eu

Material Yarn type Yarn quality Primary backing Secondary backing Waterpermeability	8.000 / 8 dTex PE monofil. Environmental friendly, from 100% PP with fibre locked Black Latex compound with 836 gr/m2	E & PE Monofilament curled (UV Stabilized) ilament straight & 5.000 / 8 dTex PE monofilament curled ree of lead and cadmium d fleece, black, UV Stabilized, Weight 135 gr/m2 rith a base of styrenebutadiene (SBR), with drainage holes, Weight
Yarn quality Primary backing Secondary backing	Environmental friendly, fro 100% PP with fibre locked Black Latex compound wit 836 gr/m2	ree of lead and cadmium d fleece, black, UV Stabilized, Weight 135 gr/m2
Primary backing Secondary backing	100% PP with fibre locked Black Latex compound wit 836 gr/m2	d fleece, black, UV Stabilized, Weight 135 gr/m2
Secondary backing	Black Latex compound with 836 gr/m2	
	836 gr/m2	ith a base of styrenebutadiene (SBR), with drainage holes, Wei
Waterpermeability		
Waterpermeability		
	60 liter/min/m2	
Pile height	26 mm	
Face weight	1.350 gr/m2	± 10%
Total weight	2.321 gr/m2	± 10%
Tuft gauge	3/8 gauge	
Stitches per 10 cm linear	16.5	± 1
Stitches per m2	17.325	± 10%
Colour	Mix of light and dark green + Field-Jute thatch	
UV stability	Meets DIN 53387 Standard (6000 hours)	
Colour fastness	Xenon Test: Blue Scale > 7, Grey-scale > 4	
Colour lining	Not Applicable	
Roll width	200 cm, 400 cm	
Roll length	20-25m	
Applications	Gardens, Landscaping, Terraces	
Infill advice	Silica sand, gradation 0,5 - 1,0 mm, 80% roundshaped, appr. 3 - 4 kg/m2	
Comments	Before installation make sure the rolls are from the same production code (first five digits the roll number) Project.	







Condor Grass has the right to alter each product specification in order to improve the carpet according to the newest technological applications. Condor Grass is not legally liable in case of non-compliance with the above-mentioned specifications. The above mentioned specifications are for reference, and can only be used informal.

